



Instalation Instructions for Marble-Lite Shower Pans


PansThese installation instructions can be applied to any of the following Marble-Lite shower pans: Standard, square, neo-angle, trench drain and custom size. Please read carefully before installing your shower pan.


•All shower pans rest on sub-floors, not finished floors. Marble-Lite cast marble shower pans have been checked before leaving the shop. They have been custom designed to drain properly if installed on a level surface.

•DO NOT use either the integral flanges or the leak-proof plastic flanges to lift the pan. They are not handles and it is critical that they are not damaged or broken in any way during installation. They ensure the pan will not leak in the event there is a drainproblem and water overflows the basin. They also prevent water from getting behind the wall.









Do not lift pan by either the integral flange or the separate flange.

• Most floors are not level. It is best to check the floor for level before installing the pan. If the floor is not level, float the floor withmortar or another suitable material and allow the material to dry before setting the pan.

• Showers with seperate plastic or fiberglass flanges, should be glued and sealed with a high quality silicone adhesive. Adhesive should be applied where the flange contacts the shower.

•The floor should be clean and free of dust and debris before setting the pan in place. After setting the pan in place, you mustcheck it in all 4 corners and diagonally in each direction for level. Shim all necessary areas to level the pan to make sure it doesnot move or rock at all.

• STANDARD INSTALLATION: The plumber should connect the drain to the pan and set the pan in place. Substrate material (sheet rock, etc.) should not be installed until after the plumber has connected the plumbing to the pan. The substrate material should stop about 1/4" above the flange of the pan.

If you have any questions call us at 305-57-8766